

Gasoline Engine Mobile Milking Machine with High Productivity and Stainless Steel Milk Bucket

Our Product Introduction

for more products please visit us on mobilemilkingmachine.com

Basic Information

- Place of Origin: Jiangsu, China
- Brand Name: HL
- Minimum Order Quantity: 10
- Price: CN¥4,015.09



Product Specification

- Model: HL-JN08
- Power Source: Gasoline / Petrol
- Operating Principle: Vacuum Pump
- Dimensions: 860x800x1040mm
- Weight: 100kg
- Vacuum Degree: 0.04-0.05Mpa (adjustable)
- Pulsation Times: 60-80 Times Per Minute
- Pulsation Rate: 60:40
- Vacuum Pump Capacity: 250 L/min
- Gasoline Motor Speed: 1800 R/min
- Milk Bucket Capacity: 25L
- Productivity (Cows): 10-12 Cows/hour (Single Bucket), 20-24 Cows/hour (Double Bucket)
- Productivity (Goats): 20-30 Goats/hour (Single Bucket), 40-60 Goats/hour (Double Bucket)
- Milk Bucket Quantity: 1 Piece (Single Bucket), 2 Pieces (Double)



More Images



Product Description

Gasoline Engine Mobile Milking Machine for Cows

P-Quick Details

Product Overview

Model HL-JN08 gasoline engine mobile milking machine operates on vacuum pump technology, providing reliable milking capability without electricity dependency. Ideal for power shortage areas, this portable solution supports various animals including cows, cattle, goats, and sheep with interchangeable milk cup groups.

Key Advantages

- Gasoline/petrol powered operation - no electricity required
- Suitable for power shortage areas
- Versatile application for cows, cattle, goats, sheep
- Optional electric motor conversion available
- Single or dual milking bucket configurations

Complete System Components

Milking Bucket Group

- 2× 25L stainless steel milk buckets
- 2× 240cc milk collector/claw
- 1× pneumatic milk pulsator
- 8× stainless steel milk shell
- 8× rubber milk inflation/liner
- 8× rubber short pulse tube
- 2× 2.8M transparent milk tube
- 2× 2.8M transparent twin pulse tube

Vacuum Pump System

- 1× 250L vacuum pump
- 1× gasoline engine
- 1× vacuum tank
- 1× vacuum regulator
- 1× vacuum meter/gauge
- 1× stainless steel silencer/muffler
- 1× plastic oil pot/can

P-Description

Design Features

- Heavy duty wheels for easy mobility
- Wire cabinet for safe operation
- Single or double milking bucket options
- Stainless steel muffler for noise reduction
- Stainless steel frame for easy maintenance
- Stable vacuum and pulsation rate for ideal milk production
- Minimal vacuum fluctuations for animal comfort

P-Benefits

Technical Specifications

Parameter	HL-JN08 (Single Bucket)	HL-JN08 (Double Bucket)
Vacuum Degree	0.04-0.05Mpa (adjustable)	0.04-0.05Mpa (adjustable)
Pulsation Times	60-80 times per minute	60-80 times per minute
Pulsation Rate	60:40	60:40
Power Fitted	0.75kw	1.1kw
Productivity (Cows)	10-12 cows/hour	20-24 cows/hour
Productivity (Goats)	20-30 goats/hour	40-60 goats/hour
Vacuum Pump Capacity	250 L/min	250 L/min
Gasoline Motor Speed	1800 r/min	1800 r/min
Bucket Quantity	1 piece (25L)	2 pieces (25L)

P-Application

Application & Versatility

This gasoline engine mobile milking machine is designed for small dairy farms and individual farmers. The system accommodates different animals including cows, cattle, goats, and sheep by simply changing the milking cluster group.







Chuangpu Animal Husbandry Technology (Suzhou) Co., Ltd.

☎ 0086 13301569240

✉ sales2@dairymachinery.cc

🌐 mobilemilkingmachine.com

Nanzhuang Village, Economic Development Zone, Yangshe Twon, Zhangjiagang City, China