

## 5000mm Height TMR Feed Mixer For Cow And Sheep Farm , Agriculture Feed Loader

Our Product Introduction

for more products please visit us on mobilemilkingmachine.com

### Basic Information

- Place of Origin: Jiangsu,China
- Brand Name: HL
- Certification: CE ISO SGS
- Model Number: HL-Q5000
- Minimum Order Quantity: 1 Set
- Price: Negotiation
- Packaging Details: Standard Packaging
- Delivery Time: 5-10 Working Days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 20 Sets/Month



### Product Specification

- Walking Type: Hydraulic Motor + Different Speed Drive Axle
- Transferring Type: Hydraulic Motor + Chain
- Turning Type: Hydro-cylinder + Swinging Steering Axle
- Feed/Silage Loading Revolving Speed: 210r/min
- Quantity Of Taking Blades: 84 Pcs
- Walking Speed: 5KM/Hour
- Highlight: **small tmr mixer, vertical feed mixer**



### More Images



## Product Description

### 5000mm Height Vertical TMR Mixers For Cow And Sheep Farm , Agriculture Feed Loader

#### Parameters of Silage Loader For cow And Sheep Farm , Agriculture Feed Loader :

Model	HL-Q5000
Feed/Silage Loading Height	5000mm
Feed/Silage Loading Revolving Speed	210r/min
Feed/Silage Loading Power	7.5KW
Quantity of Taking Blades	84 pcs
Hydraulic Power	5.5KW
Walking Speed	5KM/Hour
Walking Type	Hydraulic Motor + Different Speed Drive Axle
Transferring Type	Hydraulic Motor + Chain
Turning Type	Hydro-cylinder + Swinging Steering Axle
Lifting Type	Hydro-cylinder
Tyre Model	Front Tyre:650-16    Back Tyre:550-16
Operating and Control Type	Handle Button Switch
Dimension(L*W*H)	5750*1600*3300 mm
Machine Weight	2250KG

#### Features of Silage Loader For cow And Sheep Farm , Agriculture Feed Loader :

- A. Feed/Silage Loading section is level, to prevent secondary fermentation forage;
- B. Feed/Silage Loading roller blade is made of high quality alloy blades, durable and smooth cutting;
- C. Feed/Silage Loading height 5 m, loading height of 2.9 meters, and it can be working with the vehicle-mounted, towed working;
- D. Feed/Silage Loading efficiency  $\geq 30$  tons / hour, more efficient than similar products;
- E. The chain scraper is made of thicker square tube, to prevent stress and deformation;
- F. The whole frame is made of thick material, the weight two tons of machine itself can eliminate accidents caused by the machine wobble while working;
- G. The device uses a hydraulic brake, automatic braking when working;
- H. Self-propelled design, easy to operate on farm;
- I. Feed/Silage Loader is highly suitable for a variety of silo;
- J. Reducing labor, labor time, reduce labor intensity;
- K. Electric drive, significantly reducing the cost of Feed/Silage Loading;
- L. Improve silage quality and prevent secondary fermentation;
- M. Reduce the incidence of cows;





**Contact us:**

HAILIAN PACKAGING EQUIPMENT CO., LTD  
ZHANGJIAGANG CHUANGPU MACHINERY CO.,LTD  
**Mr.Savior Chen**



**EMAIL:** sales1@dairymachinery.cc



**MOBILE:** +86 13301568240(**Whatsapp/Viber**)



**SKYPE:** savior.chen2



**WECHAT:** savior\_chen2



**QQ:** 1003668592



**Hailian Packaging Equipment Co.,Ltd**



0086 13301569240



sales2@dairymachinery.cc



mobilemilkingmachine.com

Nanzhuang Village, Economic Development Zone, Yangshe Twon, Zhangjiagang City, China