



Milk Machine Parts Fiber Vane Milking Vacuum Pump Replacement

Basic Information

Place of Origin: China Mainland

Brand Name: HL
Certification: ISO
Model Number: HL-V01
Minimum Order Quantity: 1 set
Price: Negotiable
Packaging Details: Wooden Crate
Delivery Time: 5 - 7 days

• Payment Terms: T/T, Western Union, Pypal

• Supply Ability: 500 sets / month



Product Specification

• Item: Vacuum Pump Fiber Vane

Model: HL-V01
 Length: 150mm
 Width: 55mm
 Thickness: 6mm

• Vacuum Pump: 850L Vacuum Pump

• Highlight: surge milker vacuum pump,

dairy vacuum pump



More Images





Product Description

Milk Machine Parts Fiber Vane Milking Vacuum Pump Replacement

Quick Details:

Name: vacuum pump fiber vane , milking vacuum pump replacement Size: 150x55x6mm Material: fiber Range: apply to 250L vacuum pump

Vacuum Pump Information:

- Model: HL-V850Capacity: 850LMaterial: cast iron
- Vacuum pump degree: 50Kpa with adjustable
- Motor: 3kw
- Range: used for milking machine and milking parlor system

Features

- The fiber vane has a higher flexural strength, it is not easy to deformation and bending.
- It has smaller density than iron, so the centrifugal force is small, it will not wear casing wall.
- With high temperature resistance, it is suitable for 350 800 °C.
- With high hardness, on the premise of sufficient oil lubrication, the vacuum pump is very abrasion resistant and durable.

Application

The vacuum pump fiber vane is one of most important part for the vacuum pump which is the heart of the milking machine. The function of vacuum pump is to extract air from the milking machine system through the belt driven.

Description:

The vacuum pump fiber vane is made of phenolic resin fiber material, named Kevlar. It is the wearing part of vacuum pump, and vacuum pump is the heart of the milking machine. Regular servicing helps preserve the vacuum reserve. Various capacity vacuum pump need different specification vacuum pump pallet. The heavy duty body of the rotary vane vacuum pump is constructed from chemical resistant cast iron, making it durable to any environmental working conditions.

The function of vacuum pump is to extract air from the milking machine system through the belt driven. Thismilking machine vacuum pump gives flexibility with speeds ranging from about 800-1500 r/min and a corresponding angel of pump capacities to suit different sizes of milking machines.

Specification:

opoomounom						
Capacity (L/min)	250	300	550	850	1500	2100
Pump Speed (r/min)		1440	1440	1440	1440	1440
Vacuum Degree(Kpa)	50	50	50	50	50	50
Noise (Db(A))		≤50	≤60	≤70	≤70	≤70
Ultimate Vacuum(Mp	≤90	≤90	≤90	≤90	≤90	≤90
Motor Power(kw)	1.1	1.1	2.2	3	4	5.5
Weight(kg)	13.5	14	31	36	57.5	69.5
Size(L×W×H) (mm)	230*220*22 0	230*220*22 0	280*270*22 0	300*220*22 0	430*230*23 0	390*290*29 0

Note: The above parameters for reference only!





伊创普。

Hailian Packaging Equipment Co.,Ltd



0086 13301569240



sales2@dairymachinery.cc



e mobilemilkingmachine.com

Nanzhuang Village, Economic Development Zone, Yangshe Twon, Zhangjiagang City, China